


# EXTERNAL TOOTH LOCKWASHERS



Nominal Washer Size			Inside Diameter		Outside Diameter		Thickness	
			Max	Min	Max	Min	Max	Min
			#2	0.086	0.095	0.086	0.189	0.177
#3	0.099	0.109	0.102	0.235	0.220	0.016	0.010	
#4	0.112	0.123	0.115	0.260	0.245	0.018	0.012	
#5	0.125	0.136	0.129	0.285	0.270	0.020	0.014	
#6	0.138	0.150	0.141	0.320	0.305	0.022	0.016	
#8	0.164	0.176	0.168	0.381	0.365	0.023	0.018	
		0.204	0.195	0.410	0.395	0.024	0.018	
#12	0.216	0.231	0.221	0.475	0.460	0.027	0.020	
14	0.250	0.267	0.256	0.510	0.494	0.028	0.023	
5/16	0.3125	0.332	0.320	0.610	0.588	0.034	0.028	
3/8	0.375	0.398	0.384	0.694	0.670	0.040	0.032	
7/16	0.438	0.464	0.448	0.760	0.740	0.040	0.032	
1/2	0.500	0.530	0.513	0.900	0.880	0.045	0.037	
9/16	0.5625	0.596	0.576	0.985	0.960	0.045	0.037	
5/8	0.625	0.663	0.641	1X70	1.045	0.050	0.641L	
3/4	0.750	0.795	0.768	1.260	1.220	0.055	0.047	
7/8	6.875	0.927	0.897	1.410	1.380	0.060	0.052	
1	1.000	1.060	1.025	1.620	1.590	0.067	0.059	

<b>Description</b>	A hardened circular washer with twisted prongs or "teeth" which extend out from the outer edge of the washer.
	<b>Advantages</b>
	This is the most preferable of all tooth-lock washers. It offers the greatest locking efficiency since the teeth are on the largest radius and provide greater torsional resistance.