


FLAT SPRING NUTS



Tinnerman® Part Number	Screw Size	Length	Width	Material Thickness	PERFORMANCE DATA	
					Recommended Installation Torque (lb.-in.)	Ultimate Tensile Strength (lb.)
					Max	Min
C105SS-440-4	4/40	.44	.25	.012	3	100
C430-1032-4	10/32	.75	.44	.017		
C7000-4-4	4A or B	.38	.25	.022	9	300
C7000-632-4	6/32	.44	.28	.017	6	156
C7000-6-4	6A or B	.50	.31	.025	12	425
C7000-832-4	8/32	.50	.31	.017	8	189
C7000-8-4	8A or B	.63	.41	.028	20	534
C7000-1024-4	10/24	.63	.38	.022	14	274
C7000-10-4	10A or B	.75	.50	.031	35	672

Description	A one piece, self-locking fastener made of spring steel. The perimeter of the nut is rectangular in shape. Some variations have an arched base and/or corners which are trimmed or turned.
Applications/ Advantages	It reduces inventories by eliminating need for lock washers and spanners. Its single thread engagement design makes it easy to apply and remove. Parts are reusable. Provides the correct amount of spring tension without damaging enamel, glass or porcelain surfaces.
Material	SAE 1050 or higher carbon steel, with the exception of part# C105SS-440-4 which is made of stainless steel.
Hardness (Steel)	For material thickness 0.017-0.024 in., Rockwell 30N C40 minimum, C50 maximum. For material thickness 0.025-0.039 in., Rockwell 45N C40 minimum, C50 maximum.
Plating	See Appendix-A for information on the plating of steel spring nuts.