


# NYLON INSERT STOP NUTS



Nominal Size or Basic Thread Diameter		Steel, Zinc-plated		Width Across Flats			Thickness		Side Height	Width Across Corners
		Coarse	Fine	Basic	Max	Min	Max	Min	Ref	Ref
#4	0.1120	21NTM-40	--	1/4	0.251	0.243	0.124	0.094	0.075	0.268
#6	0.1380	21NTM-62	--	5/16	0.313	0.305	0.140	0.110	0.090	0.339
#8	0.1640	21NTM-82	--	11/32	0.345	0.336	0.187	0.157	0.110	0.374
#10	0.1900	21NTM-04	21NTM-02	3/8	0.376	0.367	0.187	0.157	0.110	0.410
1/4	0.2500	21NTE-040	21NTE-048	7/16	0.439	0.430	0.218	0.188	0.125	0.482
5/16	0.3125	21NTE-058	21NTE-054	1/2	0.502	0.492	0.265	0.235	0.158	0.552
3/8	0.3750	21NTE-066	21NTE-064	9/16	0.564	0.553	0.281	0.251	0.150	0.622
7/16	0.4375	21NTE-074	21NTE-070	5/8	0.627	0.615	0.328	0.298	0.225	0.694
1/2	0.5000	21NTE-083	21NTE-080	3/4	0.752	0.741	0.328	0.298	0.190	0.837
9/16	0.5625	--	21NTE-098	7/8	0.877	0.865	0.374	0.344	0.225	0.978
5/8	0.6250	21NTE-101	21NTE-108	15/16	0.940	0.928	0.406	0.376	0.265	1.051
3/4	0.7500	41NTE-120	41NTE-126	1-1/8	1.064	1.052	0.421	0.391	0.288	1.191
7/8	0.8750	--	41NTE-144	1-1/4	1.252	1.239	0.484	0.454	0.340	1.403
1	1.0000	--	41NTE-164	1-7/16	1.440	1.427	0.578	0.516	0.405	1.615

<b>Description</b>	Identical to a standard pattern nylon-insert stop nut but not as thick from top to bottom.	
<b>Applications/Advantages</b>	Same general applications as the standard pattern, but thin pattern nuts are used when an insufficient number of projecting threads are present to use a standard nylon insert nut.	
<b>Material</b>	<i>Steel</i>	<i>Stainless</i>
	#4 through 5/8" diameters: AISI 1008 - 1010 or equivalent steel. 3/4" through 1" diameters: AISI C1117 or equivalent steel.	18-8: Type 303 or equivalent stainless steel
<b>Hardness</b>	Rockwell C 28 maximum	1/4 through 5/8"-- Rockwell 695 - C32; 3/4 through 1-1/2"-- Rockwell B80 - C32
<b>Proof Load</b>	Thin pattern nylon insert nuts are intended for use in limited clearance applications and not for load bearing purposes. If a precise engineering standard is required, parts should be laboratory tested.	
<b>Plating</b>	Steel nylon insert stop nuts are usually supplied with zinc plating.	Stainless nylon insert stop nuts are usually provided without any additional plating.