


PHILLIPS HEX WASHER HEAD



Nominal Size	A		W	H		F		U		M	G	N	Recess Penetration Gaging Depth		Phillips Driver Size
	Width Across Flats		Width Across Corners	Height of Head		Diameter of Washer		Thickness of Washer		Dimensions of Recess					
	Max	Min	Min	Ma	Min	Max	Min	Max	Min	Ref	Ref	Ref	Max	Min	
4	.188	.181	.202	.060	.049	.243	.225	.019	.011	.096	.055	.017	.056	.040	1
6	.250	.244	.272	.093	.080	.328	.302	.025	.015	.168	.094	.029	.095	.072	2
8	.250	.244	.272	.110	.096	.348	.322	.031	.019	.168	.094	.029	.095	.072	2
10	.312	.305	.340	.120	.105	.414	.384	.031	.019	.176	.102	.030	.103	.080	2
1/4	.375	.367	.409	.190	.172	.520	.480	.050	.030	.262	.144	.035	.139	.116	3

Nominal Size	A		W	H		F		U		M		G	Phillips Size	
	Width Across Flats		Width Across Corners	Height of Head		Diameter of Washer		Driver Thickness of Washer		Dimensions of Recess				
	Max	Min	Min	Max	Min	Max	Min	Max	Min	Diameter		Depth		
4	.188	.181	.202	.060	.049	.243	.225	.019	.011	.102	.089	.063	.047	1
6	.250	.244	.272	.093	.080	.328	.302	.025	.015	.164	.160	.086	.079	2
8	.250	.244	.272	.110	.096	.348	.322	.031	.019	.188	.176	.120	.114	2
10	.312	.305	.340	.120	.105	.414	.384	.031	.019	.174	.161	.106	.083	2
1/4	.375	.367	.409	.190	.172	.520	.480	.050	.030	.233	.220	.156	.133	3