


METRIC SET SCREWS DOG POINT



| Nominal Size | Thread Pitch | Point Diameter | | Socket Size Across Corners | Socket Size Across the Flats | | Screws Below this Length are Short Sizes | Key Engagement (Min) | | Dog Point Length (short sizes) | | Dog Point Length (long sizes) | | Min Length of Screw for Torque Test | Test Torque N.m |
|---------------------|--------------|----------------|-------|----------------------------|------------------------------|--------|------------------------------------------|----------------------|------------|--------------------------------|----------------|-------------------------------|-------|-------------------------------------|--------------------|
| | | Max | Min | Min | Max | Min | | Short Sizes | Long Sizes | Max | Min | Max | Min | | |
| M1.6 | 0.35 | 0.80 | 0.55 | 0.803 | 0.724 | 0.711 | 3 | 0.7 | 1.5 | 0.65 | 0.40 | 1.05 | 0.80 | | |
| M2 | 0.4 | 1.00 | 0.75 | 1.003 | 0.902 | 0.889 | 4 | 0.8 | 1.7 | 0.75 | 0.50 | 1.25 | 1.00 | | |
| M2.5 | 0.45 | 1.50 | 1.25 | 1.427 | 1.295 | 1.270 | 5 | 1.2 | 2 | 0.88 | 0.63 | 1.50 | 1.25 | | |
| M3 | 0.5 | 2.00 | 1.75 | 1.73 | 1.545 | 1.520 | 6 | 1.2 | 2 | 1.00 | 0.75 | 1.75 | 1.50 | 5 | 0.9 |
| M4 | 0.7 | 2.50 | 2.25 | 2.3 | 2.045 | 2.020 | 8 | 1.5 | 2.5 | 1.25 | 1.00 | 2.25 | 2.00 | 6 | 2.5 |
| M5 | 0.8 | 3.5 | 3.2 | 2.87 | 2.560 | 2.520 | 8 | 2 | 3 | 1.50 | 1.25 | 2.75 | 2.50 | | |
| M6 | 1 | 4.0 | 3.7 | 3.44 | 3.071 | 3.020 | 10 | 2 | 3.5 | 1.75 | 1.50 | 3.25 | 3.00 | 8 | 8.5 |
| M8 | 1.25 | 5.5 | 5.2 | 4.58 | 4.084 | 4.020 | 12 | 3 | 5 | 2.25 | 2.00 | 4.3 | 4.0 | 10 | 20 |
| M10 | 1.5 | 7.00 | 6.64 | 5.72 | 5.084 | 5.020 | 16 | 4 | 6 | 2.75 | 2.50 | 5.3 | 5.0 | 12 | 40 |
| M12 | 1.75 | 8.50 | 8.14 | 6.86 | 6.095 | 6.020 | 20 | 4.8 | | 3.25 | 3.00 | 6.3 | 6.0 | 16 | 65 |
| M16 | 2 | 12.00 | 11.57 | 9.15 | 8.115 | 8.025 | 25 | 6.4 | 10 | 4.3 | 4.0 | 8.36 | 8.00 | 20 | 160 |
| M20 | 2.5 | 15.00 | 14.57 | 11.43 | 10.115 | 10.025 | 30 | 8 | 12 | 5.3 | 5.0 | 10.36 | 10.00 | 25 | 310 |
| M24 | 3 | 18.00 | 17.57 | 13.72 | 12.142 | 12.032 | 35 | 10 | 15 | 6.3 | 6.0 | 12.43 | 12.00 | 30 | 520 |
| Tolerance on Length | | 2-3mm: ±0.2 | | | 4-6mm: ±0.24 | | | 8-10mm: | | | 12-16mm: ±0.35 | | | | |
| | | 20-30mm: ±0.42 | | | 35-50mm: ±0.5 | | | 55-60mm: ±0.6 | | | | | | | |

| | |
|---------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Description | A headless screw threaded the entire length with a metric thread pitch. It has a protruding tip with a flat surface at the end opposite that of the hexagonal drive. |
| Applications/ Advantages | Dog point set screws are intended for permanent setting. The point should fit closely to the diameter of the drilled hole or against the flat. Often used instead of a dowel pin. |
| Material | Metric socket set screws shall be made from an alloy steel which conforms to the following chemical composition requirements-- <i>Carbon: 0.19-0.50%; Phosphorous: 0.05% maximum; Sulfur: 0.05% maximum; Lead: 0.35% maximum.</i> Set screws shall also contain one or more of these following elements: chromium, nickel, molybdenum, vanadium or boron. |
| Heat Treatment | Metric socket set screws shall be heat treated by quenching in oil from above the transformation temperature and then tempered by reheating to meet the hardness requirements listed below. |
| Hardness | Rockwell HRC 45 - 53 (Vickers HV 450 - 560) |
| Torsional Strength | Metric socket set screws of a sufficient length to be tested (as listed in the above table) shall withstand application of the test torque specified in said table without evidence of the socket reaming or the screw bursting. |
| Plating | Metric socket set screws are usually supplied with a thermal black finish. |