

TRUSS HEAD SELF-TAPPING SCREW



Nominal Size	Head Diameter		Height of Head		Slot Width		Slot Depth		Dimensions of Recess				Phillips Driver Size
	Max	Min	Max	Min	Max	Min	Max	Min	Diameter		Depth	Width	
									Max	Min	Max	Min	
4	.257	.241	.069	.059	.039	.031	.040	.030	.112	.099	.069	.018	
6	.321	.303	.086	.074	.048	.039	.050	.037	.158	.145	.084	.027	
8	.384	.364	.102	.088	.054	.045	.058	.045	.173	.160	.099	.029	
10	.448	.425	.118	.103	.060	.050	.068	.053	.188	.175	.115	.030	2
12	.511	.487	.134	.118	.067	.056	.077	.061	.248	.235	.128	.032	
1/4	.573	.546	.150	.133	.075	.064	.087	.070	.263	.250	.143	.033	3
5/16	.698	.666	.183	.162	.084	.072	.106	.085	.352	.339	.193	.059	
3/8	.823	.787	.215	.191	.094	.081	.124	.100	.383	.370	.226	.063	4

Nominal Size	Head Diameter		Recess Depth	
	Max.	Min.	Max.	Min.
	10	.516	.441	.134