


ELEVATOR BOLT



Nominal Size	E		A			H		O		P	
	Body Diameter		Head Diameter			Head Height		Square Width		Square Depth	
	Max.	Min.	Max. Edge Sharp	Min. Edge Sharp	Min. Edge Flat	Max.	Min.	Max.	Min.	Max.	Min.
1/4	0.260	0.237	1.008	0.969	0.938	0.098	0.078	0.280	0.245	0.219	0.188
5/16	0.324	0.298	1.227	1.188	1.157	0.114	0.094	0.342	0.307	0.250	0.219
3/8	0.388	0.360	1.352	1.312	1.272	0.145	0.125	0.405	0.368	0.250	0.219
Tolerance on Length		Nominal Bolt Size			Nominal Bolt Length						
					Up to 1 inch	Over 1 inch to 2-1/2 inch	Over 2-1/2 inch to 4 inch				
		1/4 thru 3/8			+0.02, -0.03		+0.02, -0.04	+0.04, -0.06			

Description	Bolt with a wide, countersunk flat head, a shallow conical bearing surface, an integrally-formed square neck under the head, and a unified thread pitch.
Applications/Advantages	Popular use is in conveyor systems.
Material	AISI 1006 - 1050 or equivalent steel.
Core Hardness	1/4 through 3/8 in. diameter, all lengths: Rockwell B70 - B100
Proof Load	1/4 through 3/8 in. diameter, all lengths: 33,000 psi.
Yield Strength	1/4 through 3/8 in. diameter, all lengths: 36,000 psi. minimum
Tensile Strength	1/4 through 3/8 in. diameter, all lengths: 54,000 psi. minimum
Elongation	18% minimum (all sizes)
Reduction of Area	35% minimum (all sizes)
Minimum Thread Length	The minimum length of thread shall be equal to twice the basic bolt diameter plus 0.25 inch